


# Product Data Sheet

## Inspection Chamber KS 10

Order No. 4010



Inspection chamber for protection and inspection of roof outlets for extensive green roofs and gravel roofs, with extension pieces also suitable for intensive green roofs.



### Technical Data

#### Inspection Chamber KS 10

Order No. 4010

Made of plastic-coated aluminium with lateral slots for water passage. Detachable and walkable cover made of galvanized, plastic-coated steel with two finger holes. If required, the interlocks can be installed into these holes.

Colour:

old silver-antique

Height:

ca. 100 mm

Outside dimensions

at transportation:

ca. 300 x 300 mm

with extended flanges:

ca. 300 x 540 mm

Slot width:

ca. 3 mm

Weight:

ca. 3.3 kg

#### Accessories:

Extension Piece KSA 8

Order No. 4008

Extension Piece KSA 20

Order No. 4020

for elevation of KS 10 in segments of 80 mm or 200 mm.

Set of interlocks

Order No. 9031

consisting of two interlocks, for easy installation into the finger holes and one square spanner.

Also available as KS 6 with 60 mm of height

Order No. 4006

### Features

- low transport volume, yet fix positioning achieved by superimposed load when installed
- registered as utility model
- fits all outlets, up to a 230 mm diameter
- walkable, corrosion-resistant
- fine lateral slots allow for an installation in bulk material too
- elevation with additional extension pieces
- separately available: set of interlocks for easy installation into the finger holes

### Application Example



Pull out flange - inside the chamber for easy transportation and storage



Pull out flange - pulled out prior to installation

### Specification Suggestion

Inspection chamber made of plastic-coated aluminium, cover made of galvanized and plastic-coated steel; colour: old silver-antique, with pull out flange at two opposite sides and with vertical drainage slots along the sides, height ca. 100 mm, load bearing capacity Class H, according to German Standard DIN 19599, slots for water

passage according to German Standard DIN 1986; delivery and installation above the outlet, with or without set of interlocks (please delete as appropriate).

Make: ZinCo Inspection Chamber KS 10  
Enquiries: ZinCo GmbH,  
Phone: +49 7022 6003-0