


Inspection Chamber KS 30 Stainless Steel



fillable or plantable cover

Inspection chamber of high-quality stainless steel for protection and inspection of roof outlets in intensive green roofs.

Technical Data

Inspection Chamber KS 30

Order No. 4035

Stainless steel, lockable; with stable, slotted and walkable cover; load-distributing support surface, with lateral slots for the absorption of drainage water, incl. PE sheet collar.

Height: ca. 300 mm
 Dimensions: ca. 300 x 300 mm
 Weight: ca. 4.0 kg

Order No. 4038 comes with a fillable or plantable cover. The total height is 360 mm.

Accessories:

Extension Piece KSA 15-E

Order No. 4036

Stainless steel, for extension of the Inspection Chamber KS 30 in segments.

Height: ca. 150 mm
 Weight: ca. 1.8 kg

Features

- suitable for green roof system build-ups up to 300 mm in height
- extension pieces for vertical adjustment in segments
- walkable
- high-quality stainless steel
- with pressure distributing support surfaces
- solid detachable cover, lockable
- also with fillable or plantable cover
- with PE sheet collar for consistent filter sheet connection

Application Example

"Roof Garden"



Plant layer

System Substrate "Roof Garden"

Filter Sheet SF

Floradrain® FD 60, infilled with Zincolit® Plus

Protection Mat ISM 50

Roof construction with root resistant waterproofing

Specification Suggestion

Inspection chamber of stainless steel; with walkable slotted cover, load-distributing support surfaces and lateral perforation, dimensions ca. 300 x 300 mm, height ca. 300 mm, weight ca. 4 kg, delivery and installation according to

manufacturer instructions.

Make: ZinCo Inspection Chamber KS 30 Stainless Steel
 Enquiries: ZinCo GmbH,
 Phone: +49 7022 6003-0

